







One Trafford, Streetworks, Tatton House, 11 Caldey Road, Roundthorn Industrial Estate Manchester, M23 9LF

Telephone 07760167078

APPLICATION FOR A LICENCE TO ERECT AND USE A TEMPORARY STRUCTURE ON OR OVER THE HIGHWAY

(HIGHWAYS ACT 1980: Section 169)

On completion this application must be returned to the above address at least 3 working days before date required. The fee is £145 per street, and an additional monthly inspection fee of £140 will be required for every month thereafter, which must be paid in advance. An Invoice will be raised once the application has been paid, payment will be arranged once the application is received.

The following must be completed in full to avoid delay. A licence, if granted, will give details of the required standard of signing and guarding to be provided and the clearances to be maintained on and over the highway. Please note that if a licence is granted the structure must not obstruct access to statutory undertakers equipment and plant. All scaffolds to be erected in accordance with TG 20:13 (BS EN 12811) and the Working at Height regulations 2005

Та	permission is required (if a limited company, give the registered name and address, together with the name of the company secretary).
	Contact Telephone
	Number

State the full postal address of the property at which the works are to be carried out:		
State the names of the roads(s) on or over which the structure is required: Road (i)		
	Road (ii)	
	. 1000 ()	
Id State the type of structure(s) to be used (please tick boxes)		
	Scaffolding	
	Hoarding	
	Access Platform/Crane	

1e Scaffolds Structures only: Identify what purpose the scaffold is to be used for:

Tick	Type of Scaffold Maximum Distributed	Load on Platforms
	Inspection	0.75 kn/sq.m
	Light Duty	1.50 kn/sq.m
	General Purpose	2.00 kn/sq.m.
	Heavy Duty	2.50 kn/sq.m.
	Special Duty	3.00 kn/sq.m.

- All Scaffolds must be inspected every 7 days, and scaff tagged in accordance with the licence application
- A copy of the Scaffold Handover sheet from the Scaffold Company to the client must be submitted to the Streetworks Team before the structure is used
- Weekly Scaffold Inspection sheets should be kept on site at all times should a Streetworks Scaffold Inspector wish to see such documentation

1f Access Platforms/MEWPS/Cranes Identify what purpose the plant is to be used for:

Tick	Type of works	
	Inspection	
	Light Duty working platform	
General Purpose working		
	platform	
	Heavy Duty working platform	
	Special lifting operation	

- All Plant must be inspected daily before use, and maintained in accordance with the HASWA 1974, LOLER and PUWER regulations
- A copy of the Plant Hire sheet from the Hire Company to the client must be submitted to the Streetworks Team before the plant is used
- Maintenance Inspection records should be kept on site at all times should a Streetworks Scaffold Inspector wish to see such documentation

1g	State the period over which the licence is required:		
	from	to	

	The following information is required:- State the name and address of your Insurance Company		
	and; the expiration date of the period	d covered by the last payment of premium	
3a	In consideration of a licence being given for the erection and use of t temporary structure(s) as aforementioned, I/We undertake to ensure that necessary precautions are taken for the protection of the public against hazar arising directly or indirectly from the exercise of the said permission. Furth I/We will indemnify and keep indemnified in the sum of £5,000,000 (Five Milli Pounds) at least the Council its servants or agents from and against all cosclaims and demands arising from anything done by virtue of this Agreeme I/We will maintain in force during the life of this licence public liability insurance cover of not less than £5,000,000 (Five Million Pounds) and shall produce evidence that such insurance is in force on being requested to do so by the Council.		
3b	I/We accept that any damage to the highway or underground services or plant caused by the erection, presence or removal of the structure/s or by the works will be made good at my/our expense.		
	Signed	Witness	
	Position or Occupation	Address	
	On behalf of		
4	Provide below or on a separate sheet of paper, a sketch or plan showing the proposed location of the structure(s) including the following:-		
	a The width(s) & length(s) of the structure(s)b The width(s) of the footway(s)	widthlengthheightwidth	
	 c The width(s) of the carriageway(s) d The location of any road junctions proposed site 	width or vehicle accesses within 15m of the	
	e In the case of scaffolding or hoardi	ng the location of any hydrants, street signs or signals or other items of street bosed structure or within 5.0m of it.	

2

Public Liability Insurance

If a separate sheet of paper is used it must be securely fixed to this application.

SCAFFOLDING LICENCE - SCHEDULE OF MINIMUM CONDITIONS

GENERAL

- The licence is issued for permission to occupy the public highway. It is the responsibility of the scaffolding company to design, construct and maintain the scaffolding in accordance with current standards (BS EN 12810, BS EN 12811 and TG20:13).
- 2. Section 169 of the Highways Act 1980, states that no person shall in connection with any building or demolition work or the alteration, repair, maintenance or cleaning of any building, erect or retain on or over the highway any scaffolding or other structure unless they are authorised to do so by a licence in writing issued by the highway authority.
- 3. A licence to erect or retain a scaffold or other structure on a street will normally only be issued to the Company responsible for actually erecting the scaffolding or other structure.
- 4. If the licensee objects to any of the following conditions of the licence, the licensee may appeal to a Magistrates' Court within 21 days of the date of receipt of the licence.
- 5. The licensee is reminded that it is their responsibility to ensure that the scaffolding or other structure, is structurally sound, is properly erected to current standards and maintained, and that adequate provision is made for the safe passage of highway users.
- 6. Work may not commence until the date specified and should be carried out within any specific limitations of time and date.
- 7. Prior to the erection of the scaffold or other structure, the licensee must inform their Client of the following conditions which may affect the way they conduct their works.

CONSTRUCTION

8. The scaffold must be designed, erected and dismantled in a safe manner and maintained in a safe condition in accordance with **current standards (BS EN 12810, BS EN 12811 and TG20:13).** On site erectors must **be competent** to erect the type and form of scaffold and hold one or more of the following qualifications as appropriate:

CISRS Scaffolder Card (or for more complex scaffold structures, The Advanced Scaffolder Card), or

OSAT NVQ (of the appropriate level for the complexity of the scaffold) and/or

Certification of competence resulting from training under a recognised manufacturer/supplier scheme eg. SA-FE Manufacturers/Suppliers Specific Training Card.

PASMA standard (or equivalent)

The erection, alteration and dismantling of all scaffolds must meet the requirements of the Work at Height Regulations 2005

- 9. The scaffolding or other structure, or portion of, to be erected that day, shall be securely erected on the day of the delivery, in a safe and considerate manner, by or under the immediate supervision of a person competent and experienced in carrying out such work. Similarly, all scaffolding, hoarding or other structure, must be removed from the highway on the day it is dismantled, upon expiration of the licence or when the need for the scaffold becomes redundant.
- 10. The licensee must do such things in connection with the scaffolding, hoarding or other structure that any highway authority or statutory undertaker reasonably requests for the purpose of protecting or giving access to any apparatus belonging to or used or maintained by them.
- 11. The scaffolding must be adequately secured to the adjoining structure or externally braced to prevent displacement Scaffold standards shall be fitted with suitable base plates, with appropriate sole plates used where necessary to the satisfaction of the local highway authority. All scaffold standards shall either be painted white, or covered with approved white, or red and white material, for the first 2.5 metres above the footway/carriageway. The scaffolding shall not have any sharp ends or unprotected nuts/bolts within 2.5m of ground level. No other equipment, ladders or materials may be kept on the footway or carriageway. All lower ladders must be removed when scaffolding is not in use to prevent unauthorised access. Adequate width and height must be maintained for the safe passage of footway users. Warning signs with the warning 'DANGER MEN WORKING ABOVE' must be displayed at each end of the structure.
- 12. Suitable and sufficient measures must be taken to prevent any highway user from being struck by falling debris, material or objects. The first lift of each scaffold must be close boarded and sheeted to prevent debris, material or objects falling onto any part of the highway. Covered traffic routes or passageways must be provided where necessary. Any spillages must immediately be removed from the highway. The footway shall be kept clear for pedestrians and properly protected both day and night, so as to cause no damage or injury to the public.
- 13. Unless otherwise agreed with the local highway authority, all elevations of each scaffold (unless access only scaffolds) must be enclosed with either fine mesh netting or sheeting to prevent debris, material or objects falling onto any part of the highway. Fan guarding must also be provided where necessary. Where the pedestrian walkway continues under the scaffolding,.
- 14. Wherever practicable, scaffolding shall be kept back 450mm from the carriageway edge, up to a height of 5.5 metres, measured from the gutter level.
- 15. If any part of the scaffold is closer than 450mm to the carriageway edge, or the proposed site of the scaffolding is considered to be particularly liable to impact damage by passing vehicles, then adequately secured and properly signed, guarded and lit barriers shall be provided along the face of the structure and approved by the local highway authority.
- 16. The scaffold must be lit during the hours of darkness at each end with red warning lights and at every 6m. All projections must have red warning lights. A gantry must have white lights under it for pedestrians.
- 17. The name, address and telephone number, including "out of hours" emergency contact number, of the scaffolder for the site, shall be legibly displayed on a

board measuring 600 x 450 mm. No other notice, placard, advertisement or anything in the nature of an advertisement, shall be printed, posted, pasted, drawn, painted, shown or displayed in any way, on or from such scaffolding or other structure, without the written consent of the local planning authority (if required) and of the local highway authority, and then, only subject to the terms of such written consents.

- 18. No door forming part of any hoarding/scaffold shall be hung, so as to open outwards across any part of the public footpath.
- 19. Partially erected/incomplete scaffolds must have a name board affixed and a warning notice board indicating 'Scaffold Incomplete Not to be used'. If left overnight or unattended the incomplete scaffold must be lit.
- 20. The issuing of the licence does not exempt any vehicle in connection with the erection or dismantling from any existing traffic regulation order.

PEDESTRIANS

- 21. If proper provision cannot be made for pedestrians to pass safely beneath the scaffold or other structure on the existing footway, then an adequately signed and guarded walkway shall be erected outside the scaffolding or other structure, to the satisfaction of the local highway authority. A joint site inspection may be required and additional conditions applied.
- 22. Measures shall be taken to distance/segregate/minimise the public from the area of work where the scaffold materials are being deposited, handled and erected.

TRAFFIC CONTROL

- 23. Traffic management issues such as the use of temporary traffic signals and temporary road closures must be discussed with the local highway authority. Additional fees may apply if positive traffic management is required. Extra restrictions may be imposed by the local highway authority on routes designated as traffic sensitive.
- 24. The licensee shall comply with Chapter 8, of the Traffic Signs Manual, together with such other conditions as the local highway authority may require. A requirement when carrying out any work on the highway is that the works are adequately signed, guarded and lit as stipulated in the "Safety at Street Works and Road Works Code of Practice.
- 25. To meet the traffic management standards, personnel involved must be trained and accredited in the "Signing, Lighting and Guarding" module as prescribed in the New Roads and Street Work Act 1991. A Company must have at least: (a) One Accredited Supervisor (who does not have to be on site) and b) A minimum of one Accredited Operative on site at all times when the work is being carried out.

MAINTENANCE

- 26. During the period in which the scaffolding, hoarding or other structure is allowed to stand, the whole shall be kept and maintained in good order and condition, and so as not to be injurious to the amenities of the neighbourhood and or users of the highway. All scaffold material, and associated fixtures and fittings, (including rubbish chutes, chains, ropes and lifting gear, etc.) must be of good condition, sound material, and adequate strength and free from patent defect. When chutes, lifting gear of other devices are used for the removal of debris all necessary precautions must be taken for the safety of all highway users. During this operation the skip or lorry body must be sheeted down to minimise dust levels.
- 27. Every hoist or pulley wheel must be adequately fenced.
- 28. Scaffold structures must be inspected daily before use by a competent person .In addition; they must always be inspected after bad or excessively dry weather or particularly high winds, which may have affected their strength and stability. The results of the inspections (including any faults found) should be recorded and made available.
- 29. At the expiration of the time for which the licence is granted, or when the work for which this consent is granted, is completed, or if the consent is revoked, whichever is first, the scaffolding, hoarding or other structure shall be immediately taken down, and notice shall be given in writing to the local highway authority.
- 30. The licensee is responsible for ensuring that the scaffolding/hoarding is kept free from fly posting and graffiti. Any occurrences must be removed within 48 hours.
- 31. A duplicate copy of the licence should be kept on site at all times during which the scaffolding, hoarding or other structures is erected, and must be readily available for inspection by authorised officers upon demand.

TIME EXTENSIONS

32. When submitting an application, if that application extends beyond the currency of the insurance certificate, the licence will be issued up to the end date of the certificate. A new certificate will need to be submitted before an extension will be considered to maintain the scaffold on site. You will not be reminded that your certificate is due for renewal.

REMOVAL

- 33. Upon removal of the scaffold, the pavement will be inspected and any damages to the highway will be made good by the local highway authority at the expense of the licensee in accordance with the provisions of Section 133 of the Highways Act 1980.
- 34. The local highway authority shall have the right to revoke the licence at any time by appropriately served notice if any of the conditions subject to which the licence is granted are not complied with and the licensee shall forthwith remove the scaffolding, hoarding or other structure. In default, and after giving notice, the Council may themselves remove the scaffolding, or other structure and any reasonable expenses incurred by the Council in doing so shall be recoverable from the licensee. Also it should be noted that failure to comply with conditions

set by the local highway authority may lead to a fine of up to £2000 being imposed (Section 169 (5) of the Highways Act 1980).

PUBLIC LIABILITY

35. Public Liability Insurance giving minimum cover of £5M for Scaffolding is required. However, it may be noted that the Council reserves the right to increase these amounts if it is considered that the site location requires a higher degree of cover. You will be notified if this is the case and proof of increased cover will be required before the licence is granted

ADDITIONAL CONDITIONS:-

- 36. The licensee is required to provide temporary ramping where pedestrians are required to follow walk ways within the carriageway to facilitate the movement of disabled pedestrians and wheelchair users.
- 37. The licensee is required to provide a minimum headroom of 2.4 metres for walkways which pass under scaffolds.
- 38. The licensee is required to provide a clear unobstructed height of 5.5 metres for any scaffold erected over a carriageway.
- 39. Where a scaffold will occupy any part of a carriageway then applicants should consult the local highway authority regarding temporary traffic management measures.
- 40. In the event that a road closure is required then a minimum of 6 weeks notice will be required.
- 41. Work cannot start on site until you have a signed licence from One Trafford